



# Ezserver JSON Client API

Revision: 01/14/24



## Content

GET /token/createtokenbased64_json?encrpty=X.....	3
GET /token/destroytoken_json?token=X.....	3
GET /server/get_content_list_json?token=X&type=X.....	3
GET /server/get_epg_list_json?token=X&name=X.....	4
GET /server/get_movie_info_json?token=X&name=X .....	4
GET /server/get_series_info_json?token=X&name=X.....	4



#### GET /token/createtokenbased64\_json?encrypt=X HTTP/1.0 \r\n\r\n

- **Parameters**
  - **encrypt**: base64-encoded string of user id and password
- **Return**
  - {"token":"X","httpport":"X","daysleft":"X"}
    - Ex. {"token":"0.123456,0.123456","httpport":"8000","daysleft":"365"}
      - Token value: 0.123456,0.123456
      - httpport: video streaming port 8000 for player
      - User expired after 365 days
  - {"token":"-2"}
    - Wrong User ID or Password
  - {"token":"-3"}
    - Time Expired

#### GET /token/destroytoken\_json?token=X HTTP/1.0 \r\n\r\n

- **Parameters**
  - **token**: the token returned by createtoken or createtokenbased64\_json
- **Return**
  - {"token":"X"}
    - Ex. {"token":"0.123456,0.123456"}
      - Token value: 0.123456,0.123456

#### GET /server/get\_content\_list\_json?token=X&type=X HTTP/1.0 \r\n\r\n

- **Parameters**
  - **token**: the token returned by createtoken or createtokenbased64\_json
  - **type**: channel, movie, series
- **Return**
  - type=channel
    - {"name":"X","stream\_type":"X","stream\_icon":"X","epg\_channel\_id":"X","category\_name":"X"}
  - type=movie
    - {"name":"X","stream\_type":"X","stream\_icon":"X","rating":"X","category\_name":"X"}
  - type=series
    - {"name":"X","cover":"X","category\_name":"X","releaseDate":"X"}



**GET /server/get\_epg\_list\_json?token=X&name=X HTTP/1.0 \r\n\r\n**

- **Parameters**
  - **token:** the token returned by createtoken or createtokenbased64\_json
  - **name:** channel name
- **Return**
  - {"id":"X","epg\_id":"X","title":"X","lang":"X","start":"X","end":"X","description":"X","channel\_id":"X","start\_timestamp":"X","stop\_timestamp":"X"}

**GET /server/get\_movie\_info\_json?token=X&name=X HTTP/1.0 \r\n\r\n**

- **Parameters**
  - **token:** the token returned by createtoken or createtokenbased64\_json
  - **name:** movie name
- **Return**
  - {"description":"X","ratingflag":"X","quality":"X","duration":"X","bitrate":"X"}

**GET /server/get\_series\_info\_json?token=X&name=X HTTP/1.0 \r\n\r\n**

- **Parameters**
  - **token:** the token returned by createtoken or createtokenbased64\_json
  - **name:** movie name
- **Return**
  - {"description":"X","ratingflag":"X","season\_no":"X","released\_date":"X"}