

11. Supported URL format

A. HTTP M3U / M3U8 URL:

Get all channels and movies with channel name, movie name, categories and icon.

- **Channel and Movie Syntax:**

- `http://ip_address:port/server/get_user_videolist?username=xxxx:password=xx
xx:video_list_type=m3u`
- `http://ip_address:port/server/get_user_videolist?username=xxxx:password=xx
xx:video_list_type=m3u8`

Examples:

- `http://192.168.0.8:17000/server/get_user_videolist?username=test:password=1
234:video_list_type=m3u`
- `http://192.168.0.8:17000/server/get_user_videolist?username=test:password=1
234:video_list_type=m3u8`

- **Channel Syntax:**

- `http://ip_address:port/server/get_user_chlist?username=xxxx:password=xxxx:
ch_list_type=m3u`
- `http://ip_address:port/server/get_user_chlist?username=xxxx:password=xxxx:
ch_list_type=m3u8`

Examples:

- `http://192.168.0.8:17000/server/get_user_chlist?username=test:password=1234
:ch_list_type=m3u`
- `http://192.168.0.8:17000/server/get_user_chlist?username=test:password=1234
:ch_list_type=m3u8`

- **Movie Syntax:**

- `http://ip_address:port/server/get_user_movielist?username=xxxx:password=xx
xx:movie_list_type=m3u`
- `http://ip_address:port/server/get_user_movielist?username=xxxx:password=xx
xx:movie_list_type=m3u8`

Examples:

- `http://192.168.0.8:17000/server/get_user_movielist?username=test:password=12
34:movie_list_type=m3u`
- `http://192.168.0.8:17000/server/get_user_movielist?username=test:password=1
234:movie_list_type=m3u8`

B. HTTP Channel URL:

By Channel No:

Syntax1: http://ip_address:port/x.ch?u=xxxx:p=xxxx

Syntax2: for secure way: http://ip_address:port/x.ch?token=x.xxxxxx,x.xxxxxx (token is created by EZserver API: createtoken or createtokebase64)

Syntax3: http://username:password@ip_address:port/x.ch

Syntax4: for HLS Streaming: http://ip_address:port/chx.m3u8?u=xxxx:p=xxxx

Syntax5: http://username:password@ip_address:port/chx.m3u8

Syntax6: for ts transcoder: http://ip_address:port/x.ch?u=xxxx:p=xxxx:muxer=ts

Syntax7: for flv transcoder: http://ip_address:port/x.ch?u=xxxx:p=xxxx:muxer=flv

Ex.

<http://172.16.10.50:8000/1.ch?u=test:p=1234>

<http://172.16.10.50:8000/1.ch?Token=0.300000,0.576543>

<http://test:1234@172.16.10.50:8000/1.ch>

<http://172.16.10.50:8000/ch1.m3u8?u=test:p=1234>

<http://test:1234@172.16.10.50:8000/ch1.m3u8>

<http://172.16.10.50:8000/1.ch?u=test:p=1234:muxer=ts>

<http://172.16.10.50:8000/1.ch?u=test:p=1234:muxer=flv>

By Channel Name:

Syntax1: http://ip_address:port/channel_name?u=xxxx:p=xxxx

Syntax2: http://username:password@ip_address:port/channel_name

Syntax3: http://username:password@ip_address:port/channel_name.m3u8

Ex.

<http://172.16.10.50:8000/robert?u=test:p=1234>

<http://test:1234@172.16.10.50:8000/robert>

<http://test:1234@172.16.10.50:8000/robert.m3u8>

C. HTTP Movie URL:

By Path:

Syntax1: http://ip_address:port/movie_path?u=xxxx;p=xxxx

Syntax2: http://username:password@ip_address:port/movie_path

Ex.

<http://172.16.10.50:8000/media/videos/Movie/1.ts?u=test;p=1234>

<http://172.16.10.50:8000/media/videos/Movie/1.flv?u=test;p=1234>

By Movie Name:

Syntax1: http://ip_address:port/movie_name?u=xxxx;p=xxxx

Syntax2: http://username:password@ip_address:port/movie_name

Ex.

If movie name of <http://172.16.10.50:8000/media/videos/Movie/1.ts?u=test;p=1234> is

“MOVIE1”, then

<http://172.16.10.50:8000/MOVIE1?u=test;p=1234>

<http://test:1234@172.16.10.50:8000/MOVIE1>

D. RTSP Channel URL:

<rtsp://172.16.10.50:5544/1.ch?u=test;p=1234>

E. RTSP Movie URL:

<rtsp://172.16.10.50:5544/media/videos/Movie/1.ts?u=test;p=1234>

F. RTMP Link Re-Streaming:

Syntax1: rtmp://ip_address:port/live/x.ch?u=xxxx;p=xxxx

Syntax2: rtmp://ip_address:port/live/channel_name?u=xxxx;p=xxxx

EX.

<rtmp://172.16.10.50/live/1.ch?u=test;p=1234>

<rtmp://172.16.10.50/live/TV1?u=test;p=1234>